

## Standard specifications



<b>Item name</b>		LeveLuck SD 501U (Under sink type)		
<b>Feed water specs and connection</b>		Water supply valve closed type		
<b>Power supply</b>		AC120V 60Hz		
<b>Rated current</b>		3.2A		
<b>Power consumption</b>		Max. approx. 230W(If production is done at a high KANGEN pH level)		
<b>Main unit</b>	<b>dimensions</b>	13.3(H) x 10.4(W) x 6.7(D)inch / 338(H) x 264(W) x 171(D)mm		
	<b>weight</b>	13.9 lbs / 6.3kg		
<b>Ionizing system</b>		Continuous ionizing system (Built-in flow rate sensor)		
<b>Electrolysis</b>	<b>KANGEN Water</b>	1.2 ~ 2.0gal. / min. 4.5 ~ 7.5L / min.		
	<b>Feed water pressure Approx.</b>	29psi / 200kPa		
	<b>Strong Acidic Water</b>	0.2 ~ 0.3gal. / min. 0.6 ~ 1.2L / min.		
	<b>Feed water pressure Approx.</b>	15psi / 100kPa		
	<b>Electrolysis capacity settings</b>	7 levels	KANGEN Water at 3 levels Clean Water Beauty Water Strong Acidic Water Strong KANGEN Water	(Approx. pH8.5 / pH9.0 / pH9.5) (Approx. pH7.0) (Approx. pH6.0) (Approx. pH2.5) (Approx. pH11.0)
	<b>Cleaning system of ionizing cell</b>	Automatic cleaning system		
	<b>Materials of electrode and ionizing cell</b>	Platinum-plated titanium		
	<b>Water filter</b>	<b>Filter material</b>	Granulated antibacterial activated charcoal, calcium sulfite	
		<b>Removable substance</b>	Residual chlorine (Sterilizer), Odor, and Red rust	
		<b>Un-removable substance</b>	Metal ions/salt dissolved in original tap water	
<b>Replacement interval</b>		Varies according to region and water quality		
<b>Applicable water pressure</b>		7psi ~ 65psi / 50kPa ~ 450kPa (Approx. 0.5kgf/cm <sup>2</sup> ~ 4.5kgf/cm <sup>2</sup> )		
<b>Available water temperature</b>		41~95°F / 5~35°C		
<b>Electrolysis enhancer (for Strong Acidic Water production)</b>		Forced dissolving adding type		
<b>Electrolysis enhancer (sodium chloride) re-fill need indication</b>		Voice guidance, Alarm sound, LCD message		
<b>Protective device</b>	AC120V 60Hz	Current fuse 6A		
<b>Detective device</b>		Detection of temperature rise and hot water		
<b>Length of power cord</b>		Approx. 1.8 m		

• Specifications and design subject to change for product improvements without notice.

• The electrolytic processing capacity and the filter service life largely depend on the water quality or how the machine was used.